

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
1 September 2005 (01.09.2005)

PCT

(10) International Publication Number
WO 2005/080768 A1

(51) International Patent Classification⁷: **F02B 57/02**

(21) International Application Number:
PCT/IB2005/001018

(22) International Filing Date: 10 February 2005 (10.02.2005)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
P-143/04 18 February 2004 (18.02.2004) YU

KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.

(84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IS, IT, LT, LU, MC, NL, PL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

(71) Applicant and

(72) Inventor: JURISIC, Vojislav [YU/YU]; Brace Savic 3, 11273 Batajnica (YU).


(81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE,

Published:

- with international search report
- before the expiration of the time limit for amending the claims and to be republished in the event of receipt of amendments

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

(54) Title: ELLIPTICAL ROTARY MOTOR WITH INTERNAL COMBUSTION



(57) Abstract: A method and apparatus consisting of a stator (1) within which rotates rotor (2) together with work cylinder (3) and piston (6) which is via rod (7) and larger pin (9) connected with rocker (8) which via smaller pin (10) transfers rotary moment to rotor (2), i.e. to output shafts (17) and (20). At the same time rod (7), via larger pin (9) by its own motion moves satellite gears (12), which, off-center mounted bearings (13) and symmetrically geared to off-center mounted inner-tooth gears (11), define position of working cylinder (3) relative to two ODC and two IDC.



WO 2005/080768 A1